

DESCRIPTION

QuickStix is water based, solvent free, factory applied technology that is recommended for the installation of approved Commercial luxury vinyl tiles and planks over porous and non-porous substrates. QuickStix offers unmatched possibilities when dealing with high moisture and when time and ease of installation is a requirement. Using QuickStix eliminates the need for moisture mitigation and 2 parts adhesives.

APPLICATION

QuickStix may be used on porous or non-porous surfaces, such as metal, suspended wood, fiberglass, and existing properly prepared flooring, and concrete substrates with up to 99% in-situ Relative Humidity as determined per latest version of ASTM F2170, pH up to 12.0, and MVER of 18 lbs. per ASTM F1869 Calcium Chloride.

FEATURES

- Quick and easy installation
- Approved in areas with heavy rolling load and heavy static load
- Open to foot traffic immediately after installation
- No Occupancy disruption associated with traditional liquid adhesives
- High Peel and shear strength

ENVIRONMENTAL ATTRIBUTES

FloorScore Certified, solvent free, water based, low VOC, no use or transport of adhesive pails.

SUBSTRATE PREPARATION

Follow concrete substrate preparation guidelines for resilient flooring as outlined in latest version of ASTM F710. For installation over Mannington approved panel substrates follow ASTM F 1482. The substrate must be sound, flat, smooth, dry and absolutely clean. Remove any dirt, dust, wax, loose paint, existing adhesives, and concrete sealers, curing and parting agents, and all other foreign matter that would cause staining or interfere with a proper bond. The installation site must be acclimated with permanent HVAC in operation. Use only Portland based patching and leveling compounds.

Note: Below and on-grade concrete subfloors must have a suitable vapor retarder properly installed directly beneath the slab.

The room temperature, as well as flooring materials and adhesive, must be maintained between 55°- 85° F, and the relative humidity between 35%-55% for 48 hours prior to, during and after the installation. Do not use on substrates that have been chemically cleaned or abated.

MANNINGTON PREMIUM UNIVERSAL PRIMER

The use of Mannington's Premium Universal Primer is required for the installation of QuickStix products over porous or non-porous substrates. QuickStix warranty will be voided if the primer is not used.

TECHNICAL DATA

QuickStix material: Proprietary acrylic, highly plasticizer resistant
QuickStix plus release paper liner thickness: LVT product plus 0.0115" (0.29 mm)
QuickStix plus release paper liner weight: LVT product plus 0.059 lb/sq-(0.29 Kg/sq-m)
QuickStix layer only: 0.0065" (0.17 mm)
Release paper liner: Siliconized paper, 0.005" (0.13mm)

SHELF LIFE

18 Months from date of manufacture

WARRANTY

QuickStix is backed by a limited Commercial Warranty for bond and manufacturing defects. The QuickStix warranty matches the product warranty which will vary by product type.

SAFETY AND CLEAN UP

Dried adhesive may require the use of an adhesive remover such as low odor mineral spirits or equivalent. Collect and dispose release liner paper in accordance with local state and federal requirements.

DISCLAIMER: Users should determine the suitability of this information or product for their own particular purpose or application. Mannington is not responsible for the misuse of this product. For full details, please check full QuickStix Installation Instructions.

EMERGENCY CONTACTS: Product/Medical Emergency Phone Number (24 Hours): (866) 359-5602 Transport Emergency: Within the U.S. - CHEMTREC: (800) 424-9300 / Outside the U.S. - CHEMTREC: +1-703-527-3887

Choices that Work.

For more information, please contact Mannington Technical Services at 800 241 2262 Ext. 3 or visit www.manningtoncommercial.com.