

MANNINGTON MR-101

DESCRIPTION: Mannington Mr-101 Wall Base Adhesive is a premium solvent free adhesive with aggressive wet suction to grip rubber and vinyl wall base. MR-101 can be used over most interior wall surfaces with the exception of vinyl wall covering and other similar non-porous surfaces that prevent the curing of any latex-based adhesive.

DIRECTIONS:

1. Adhesive, wall base and job site must be conditioned at 65° - 80°F for 48 hours before and after installation.
2. Use only on structurally sound surfaces, dry wall, concrete block, brick, plywood, paneling, masonry, plaster, etc.
3. Apply to surfaces that are clean, dry, and free from dust, wax and grease. Remove loose paint, plaster, old adhesive and other contaminants that would interfere with adhesion.
4. Cement or plaster must be thoroughly seasoned and dry.
5. Wrapped base or rolled base should lay flat for 24 hours before application.
6. With a 1/8" square or V-notched spreader, spread on back of base or wall surface.
7. Press base firmly into place immediately after application of adhesive.

DO NOT APPLY OVER NON-POROUS SURFACES SUCH AS MASONITE, PLASTIC LAMINATES OR VINYL WALL COVERINGS.

CLEAN-UP: Wet adhesive may be removed immediately with a damp cloth. If adhesive has dried, use a cloth moistened with Mineral Spirits. Do not allow solvent to penetrate the seams; this can destroy the adhesive bond.

COVERAGE AND TROWEL RECOMMENDATION: Approximately 250 linear feet of 4" base per gallon

ON CARTRIDGES - Remove cap and insert cartridge into applicator. Use nozzle with 3 holes for 4" and 5 holes for 6" base. Apply adhesive to back of cove base. Position or roll base immediately or within 20 minutes

PHYSICAL PROPERTIES:

Weight/Gallon: 10.4

Consistency: Heavy paste

Shelf Life: One year @ 70°F in un-opened container