

# MANNINGTON COMMERCIAL

## Infinity® RE (6R)

### **CONSTRUCTION SPECIFICATIONS**

PRIMARY SUBSTRATE:	100% Synthetic
PRECOAT LAYER:	Polymeric Performance Precoat
FIRST LAYER:	Vinyl Compound
STABILIZING LAYER:	Fiberglass Reinforced Layer
SECOND LAYER:	Vinyl Composite Non-Aqueous Recycled Pre-Consumer Carpet and Resilient
RECYCLED CONTENT:	Pre-Consumer Carpet and Resilient and 10% minimum Post-Consumer recycled content by total weight of product
TOTAL BACKING WEIGHT:	104 ounces per square yard (Style Dependent)
THICKNESS:	.250 inches – (1/4" approximate)
MODULAR SIZE:	24" X 24"

### **PERFORMANCE SPECIFICATIONS**

METHENAMINE PILL TEST: (FF 1-70)	PASSES
RADIANT PANEL TEST: (ASTM E-648)	CLASS I
NBS SMOKE TEST: (ASTM E-662)	450 OR LESS (FLAMING MODE)
DIMENSIONAL STABILITY: (AACHEN)	PASSES
MOISTURE IMPACT TEST:	PASSES
WARRANTY:	LIMITED LIFETIME WARRANTY

### **ENVIRONMENTAL CERTIFICATIONS**

INDOOR AIR QUALITY:	MEETS CRI GREEN LABEL PLUS
NSF/ANSI-140:	PLATINUM
ISO14001:	CERTIFIED MANUFACTURING FACILITY