













SPECIFICATIONS | SPACIA FIRST

	CONSTRUCTION	Luxury Vinyl Tile with squared edges
	AVAILABLE SIZES	12" x 12" (305 x 305 mm), 12" x 24" (305 x 610 mm), 18" x 18" (457 x 457 mm), 6" x 36" (152 x 915 mm), 7.25" x 48" (185 x 1220 mm) Sizes are style dependent.
	OVERALL THICKNESS	0.08" (2.0 mm)
	PIECES PER CARTON	27 pcs - 12" x 12"; 19 pcs - 12" x 24"; 12 pcs - 18" x 18"; 18 pcs - 6" x 36"; 9 pcs - 7.25" x 48"
	COVERAGE PER CARTON	27 sq. ft. of 12" x 12"; 38 sq. ft. of 12" x 24"; 27 sq. ft. of 18" x 18"; 27 sq. ft. of 6" x 36"; 21.75 sq. ft. of 7.25" x 48"
	WEIGHT PER CARTON	18.87 lbs. - 12" x 12"; 28.35 lbs. - 12" x 24"; 20.55 lbs. - 18" x 18"; 19.75 lbs. - 6" x 36"; 15.54 lbs. - 7.25" x 48"
	BOXES PER PALLET	72 ct. of 12" x 12"; 60 ct. of 12" x 24"; 72 ct. of 18" x 18"; 72 ct. of 6" x 36"; 90 ct. of 7.25" x 48"
	3RD PARTY CERTIFICATION	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)
	LIGHT COMMERCIAL WARRANTY	This product is backed by our Limited 10 year Light Commercial Warranty.
	LEED	Mannington Commercial products may contribute to multiple LEED credits.
	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in eight communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.
	LOOP®	Mannington's next closed-loop recycling program, we are reclaiming and recycling end-of-life LVT into new LVT. This further extends our ability to keep post-consumer LVT out of landfills and reducing the environmental impact of our products. Contact your local Mannington representative, or call 800.241.2262 ext. 6211.
STATIC LOAD LIMIT		750 PSI
SPECIFICATIONS (ASTM F-1700)		Class 3, Type B
HEAT STABILITY (ASTM F-1514)		Passes
STAIN & CHEMICAL STABILITY (ASTM F-925)		Passes
HUD/ FHA REQUIREMENTS		Exceeds
ADA		Meets or exceeds ADA Requirements
COEFFICIENT OF FRICTION		COF ≥ 0.5 Leather; 0.6 Rubber
FLOORING RADIANT PANEL TEST (ASTM-E-648)		Passes - Class 1
N.B.S. SMOKE CHAMBER TEST (ASTM-E-662)		< 450 (non-flaming mode)
INSTALLATION ADHESIVE		Amtico 373 / Full Spread Porous & Non-Porous Subfloor, Amtico PS - High Moisture Adhesive /Transitional Pressure Sensitive/ Full Spread Porous & Non-Porous Subfloor, Amtico Universal 2-Parts/ Full Spread Non-Porous Subfloor, XpressStep Spray Adhesive / RH 90%, MVER 8, pH 11, XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH 12. <i>Note: Must use Amtico Universal 2-Parts or XpressStep Adhesive under hospital beds and heavy rolling loads or where high performance is needed.</i>

